

0.00 EUR
incl. 19% VAT, plus [shipping](#)

- NVidia Jetson Orin NX !
- 16GB RAM !
- 4 x GMSL-2 / Model M12 !



- NVIDIA® Jetson Orin™ NX SoM with 1024 CUDA Cores
- 4 x GMSL Cameras Support
- 2 x Ethernet with M12 Connectors
- 1 x CAN FD for Vehicle Connection
- 9-60VDC Input with Built-in Smart Power Management
- -25°C ~ 70°C Operating with Fanless Design
- Watchdog for System Monitoring

System

IBOX-601-G2-00-ONX16

NVIDIA® Jetson Orin™ NX 16GB / VDB-100 / 4 x GMSL-2 / Model M12

Module

NVIDIA® Jetson Orin™ NX 16GB

(1024 CUDA cores + 8-core ARM Cortex-A78AE CPU + 16 GB LPDDR5)

Security

Platform Security Controller (PSC), Security Engine (SE)

	<ul style="list-style-type: none"> - 2 x M12 X-coded for 1 x 2.5GbE & 1 x GbE (Intel® 2.5GbE, SoM Built-in GbE)
	<ul style="list-style-type: none"> - 2 x USB 3.2 Type-A * Two ports share 10Gbps bandwidth
	<ul style="list-style-type: none"> - 1 x HDMI Type-A output supports 4K resolution
	<ul style="list-style-type: none"> - 1 x HD Audio from the HDMI
Interface	<ul style="list-style-type: none"> - 1 x DB-9 for RS-232/422/485 - 4 x FAKRA for GMSL-2 cameras - 1 x DB-9 for CAN FD - 1 x USB Type-C for system recovery (Device only) - 1 x Nano SIM card slot - 5 x Pre-cut holes for external SMA antenna
	<ul style="list-style-type: none"> • 1 x M.2 2230 Key E slot
INTERNAL EXPANSION	<ul style="list-style-type: none"> • 1 x M.2 3042/52 Key B slot (USB3.0) with nano SIM card slot • 1 x mPCIe full-size slot (USB.2.0 supported)
	<ul style="list-style-type: none"> • 1 x M.2 2280 Key M slot supports NVMe SSD (Pre-installed system BSP)
STORAGE (Internal)	
Operating System / SDK	<p>NVIDIA® JetPack including Jetson Linux, NVIDIA® development tools -25°C ~ 70°C (-13°F ~ 158°F), ambient w/ 0.6m/s airflow *Operating temp. varies by accessories installed.</p>
Operating Temp.	
	<p>-40°C ~ 80°C (-40°F ~ 176°F)</p>
Storage Temp.	
Relative Humidity	<p>10% RH – 90% RH (non-condensing)</p>
Certification / Standard	<p>CE, FCC Part-15 Class A, E-mark, EN50155, EN45545-2 (R25)</p>
Vibration	<ul style="list-style-type: none"> • Random – IEC60068-2-64, random, 2.5G@5~500Hz, 1hr/axis • MIL-STD-810G – Method 514.6, Procedure I, Category 4
Shock	<p>MIL-STD-810G, Method 516.6, Procedure I, Trucks and semi-trailers=15G (11ms) with SSD</p>
Power Input	<ul style="list-style-type: none"> • 1 x M12 K-coded for DC-IN 9 ~ 60V • Supports Smart Power Management, OCP and OVP
	<p>Aluminum Alloy</p>
	<p>Fanless Passive Cooling Design</p>
Mechanical	<p>DIN-Rail, Wall Mount</p>
	<p>1770 g</p>
	<p>150 mm (L) x 135 mm (W) x 77 mm (H)</p>

WI-FI: M.2 2230 Wi-Fi Module

WWAN Modem: M.2 3042/52 WWAN Modem

GPS: mPCIe GPS Module

UPS: BAT-2300v2

Optional Accessories

GMSL Camera:

2MP 63.9° - Sony IMX390 2MP, 63.9°, GMSL-2

2MP 120.6° - Sony IMX390 2MP, 120.6°, GMSL-2

2MP 186.0° - Sony IMX390 2MP, 186.0°, GMSL-2